T Series

TI2.6 | TI2.8 | TI2.9 | TI3.9 | TI4.8 | TI5.9 | TI6.2
TO3.9 | TO4.8 | TO5.9 | TO6.2

- Full Front Maintenance
- Curved Installation
- No Light Leakage
- Climbing support
- Light and Thin

Parameter

T Series Outdoor	TO 3.9	TO 4.8	TO 5.9	TO 6.2
Pixel Pitch(mm)	3.91mm	4.81mm	5.95mm	6.25mm
Pixel Matrix Per Sq.m	65536	43264	28224	25600
Pixel Configuration	SMD1921	SMD2727/1921	SMD3535	SMD3535
Brightness (nits)	>4000	>4000	>4000	>4000
Scan	1/16	1/13	1/7	1/10
Cabinet Resolution	128x256	104x208	84x168	80x160
Power Con. (Max./Avg)	750/ 220 w/sq.m	700 / 220 w/sq.m	700 / 220 w/sq.m	710/ 210 w/sq.m
Module Dimension	250x250mm / 9.83x9.83ft			
Cabinet Dimension	500x1000x65mm / 1.64x3.28x0.20ft			
Cabinet Weight	13kg / 28.66lb (Die-casting Aluminum)			
Service Access	Front / Rear			
Rotation Angle	-10° and +10°			
Refresh Rate (HZ)	1920			
Grey Scale (bit)	16			
Viewing Angle (H/V)	160 / 160			
IP Rate	IP65			
Input Voltage (AC)	110 / 240			

* Specifications and photos are subject to change without prior notice.

T Series Indoor	TI 2.6	TI 2.9	TI 3.9	TI 4.8	TI 5.9	TI 6.2
Pixel Pitch(mm)	2.84mm	2.976mm	3.91mm	4.81mm	5.95mm	6.25mm
Pixel Matrix Per Sq.m	123904	112896	65536	43264	28224	25600
Pixel Configuration	SMD2121	SMD2121	SMD2121	SMD2121	SMD3528	SMD3528
Scan	1/32	1/28	1/16	1/13	1/7	1/10
Cabinet Resolution	176×352	168×336	128×256	104×208	84×168	80×160
Power Con. (Max./Avg)	800 / 250w/sq.m	750 / 240w/sq.m	750 / 220w/sq.m	680 / 200w/sq.m	680 / 200w/sq.m	700 / 210w/sq.m
Module Dimension	250x250mm / 9.83x0.83ft					
Cabinet Dimension	500x1000x65mm / 1.64x3.28x0.20ft					
Cabinet Weight	13kg / 28.66lb (Die-casting Aluminum)					
Service Access	Front / Rear					
Rotation Angle	-10° and +10°					
Brightness (nits)	≥1000					
Refresh Rate (HZ)	3840					
Grey Scale (bit)	16					
Viewing Angle (H/V)	160 / 160					
IP Rate	IP31					
Input Voltage (AC)	110 / 240					

* Specifications and photos are subject to change without prior notice.

Full Front Maintenance

LED modules, receiver card, hub card, power supply, cables, etc are all front service.

Quick Exchangeable Control Box For Easy Maintenance

Curved Installation

Curved with every 2.5° between -10°and 10°, which can make convex and concave.

Climbing Support

Climbing structure can help you make convenient maintenance.

No light leakage trouble

No light leakage design with specific strips on side of cabinet and behind neighbour module.

Ultra Fast Response

The response speed exceeds the response limit of the naked eyes,
while playing the high speed dynamic images in an LED Screen,
it will have more advantages, there will be no ghosting&trailing and it will perfectly provide the dynamic images.

Perfect rendering dynamic picture

Response speed

Smear, Ghosting phenomenon

Wide Viewing Angle

Both 160° from horizontal & vertical for the viewing angle.
Seeing from five directions, it would be still the natural and clear image in an LED display.

Accessories

Power Cable

Data Cable

Main Power Cable

Main Data Cable

Controller &Processor

Front Maintenance Tool

Curved Lock

Hanging Bar

sales@LEDFUL.com
+86-135-3017243/5
www.LEDFUL.com